

DH 16.000

The DH16.000 has the same specifications as the FM16.000 with the addition of a **second head**. This second head is in parallel to the first one with the tool operating from the bottom rather than from the top.

This enables creasing and perforating to be done in the same pass or, by fitting two creasing tools, creasing can be done from the top and bottom in the same pass ensuring the correct crease direction for zig zag folding.

La DH16.000 ha le stesse caratteristiche della FM16.000 a cui si aggiunge una **seconda testa** che, contrariamente all'altra, lavora dal basso verso l'alto.

Questo consente di poter realizzare in un solo passaggio cordonatura e perforazione, oppure cordonatura "positiva" e "negativa" sullo stesso foglio.



PRODUCTIVE

FAST

INGENIOUS

INDUSTRIAL



DOUBLE HEAD CREASING MACHINE CORDONATRICE DOPPIA TESTA



TECHNICAL SPECIFICATIONS

Size min/max 8 x 10 cm / 50 x 70 cm
(with optional extension feeder 50 x 100 cm)

Sheet weight from 80 to 600 g.s.m.

Programs 200 programs with 100
creasing or perforating

Min. distance creasing 0,1 mm

Production A4 with 1 crease 16.000 sheets per hour

Power supply 400 Volts three phase
+ neutro 50 Hz

Power requirement 3,5 Kw

Net weight 350 Kg

Size 180 x 90 x 120 cm

Optionals punching kit; digital creasing kit;
perforating kit 2/1 - 3/1 - 4/1 - micro perf.

AVAILABLE WITH | DISPONIBILE CON

QR CODE READER • REMOTE ASSISTANCE